

Stand Alone Controllers

WAR-STA-4EM / WAR-STA-4MF

Models Available:

Controller with built in Proximity Reader

WAR-STA-4EM----- EM Proximity; 125 KHz

Card Type:

Proximity card, EM4100 series

Controller with built in Mifare Reader

WAR-STA-4MF -----Mifare \ CPU \ RC; 13.56MHz

Card Type:

FM1208 CPU Card, Philips S50, Mifare-1 Compatible



Model	Cardholder	User PINs	Transaction	Software
WAR-STA-4EM	2550	10	10000	No
WAR-STA-4MF	2550	10	10000	Yes

Operation Modes:	Card Only, PIN Only, Card + PIN, Card / PIN
Operating Frequency:	125 KHz
Card Type:	Depends on the built-in Reader Proximity or Mifare
Read Range:	8 to 10 cm
Relay Output:	NC/NO, 30 V DC, 5A Maximum
Power Supply:	12V DC +/- 10%, 200 mA
Controller Dimensions:	108 mm(H) x 87 mm(W) x 18 mm(D)
Weight:	300 Grams

All product specifications on this brochure are subject to change without



CANADA:
351 Ferrier Street, Unit 5
Markham, Ontario
L3R 5Z2, Canada
Tel: 416-410-6865
Fax: 1-866-331-3341
Toll Free: 1-866-843-6865

USA:
700 Ensminger Rd.
Site 104 Tonawanda, NY
14150 USA
Toll Free: 1-866-843-6865
Local: 1-717-687-8736
Fax: 1-866-331-3341
www.watchnetaccess.com
info@watchnetaccess.com

UAE:
P.O. Box # 126312
Dubai, UAE
Tel: + 971 4 3584458
Fax: + 971 4 3584458
Mobile: + 971 50 5869290

INDIA:
C-48, DDA Shed, Ground Floor
Okhla Industrial Area, Phase I
New Delhi-110020
Tell: +91 11 26816005
Fax: +91 11 26816006
Mobile: + 91 9654297002